



Scanning with Simplicity



SAVEO-RNG-G2
Unified Quick Set 8

Package contents

- 1 x SAVEO-RNG-G2-**** scanner
- 1 x Modular Charge and Data Dock
- 1 x USB Type-C cable
- 2 x 550mAh Lithium-ion Rechargeable Batteries
- 1 x y Quick o Guide

Important Safety Information

Don't put scanner or dock in places of excessively high temperature, such as exposure to direct sunlight. Don't use scanner in extremely humid conditions or in conditions of extreme temperature change. Never damage the rechargeable batteries. Damaging the casing of the rechargeable battery might cause explosion or fire!

Quick Setup Mobile (Bluetooth HID)

1.) Enter Pairing Mode



Un-pair/Pair Bluetooth

2.) Enable Bluetooth on your mobile device

Go to your phone's homescreen and find "Settings", then "Bluetooth" and turn Bluetooth on. Your device will search for available devices within range.

After approx 20 seconds, Saveo Scan will appear as an external keyboard with a unique identifier serial number (SAVEO-RNG-G2-xxxxxxx).

Select the scanner from "Available Devices" and wait for pairing process to complete.

Once "Connected" is displayed, your device is paired to the scanner. Your scanner is now ready to use.

Scan this barcode code to disconnect from any previously connected devices and put the scanner into "Pairing mode".



Please Note: Devices only need to be paired once. When they are within Bluetooth range they will automatically attempt to connect to each other. If you wish to connect to another device it is recommended you first unpair this device.

Quick Setup PC/MAC (Bluetooth HID Dock)



1.) Connect Dock to USB Port



Simply connect the dock to a free USB port on your computer using the USB Cable and scan the dock's barcode to pair & connect your scanner. The dock is plug and play, so no driver is required for Bluetooth HID mode.

Transmission Modes



Direct Mode (Default)



Memory Mode



Memory Data Upload



Total Storage Count



Clear Memory

System Parameters



Factory Reset

Returns the scanner to it's factory default settings.

Transmits Firmware version information to the connected device.



Get Firmware Version

Connection Modes



Bluetooth HID (Default)

Bluetooth HID Keyboard Emulation Mode (no App required)

Bluetooth SPP Serial Port Profile Mode (requires compatible App or Driver)



Bluetooth SPP Mode



Bluetooth BLE Mode

Bluetooth BLE Serial Port Emulation Mode (requires compatible App or Driver)

Keyboard Languages



U.S. English Keyboard (Default)



French keyboard



Germany keyboard



Italy keyboard



Portugal keyboard

*For more language settings, please contact us for the complete file.

Vibration / Haptic Feedback



Disable



Enable (Default)

Standby time



Standby Immediately



1 Min (Default)



5 Mins

*For more Standby settings, please contact us for the complete file.



10 Mins

For Support, please

Contact us at:

Email: inquire@saveoscan.com

Web: www.saveoscan.com

US: +1-720-257-7070

UK: +44-208-099-8071

IRE: +353-1-685-4600



Limited Warranty

Saveo Scan provides a one year limited warranty. This warranty does not cover any product which has been subject to improper use, neglect or unauthorized repair or installation. This warranty does not cover consumable parts (Cables & batteries are consumables).